



## 022-12146 through 022-12147 Adjustable SRL Ladder Anchor System

### FEATURES :

- Galvanized steel post with top anchor extension bracket
- Powder coated stainless steel head unit
- Adjustable positioning for captive eye allowing for either sternal or dorsal D-ring harness connection
- For installation on fixed ladders only
- All mouting hardware included
- For use with all SRL types
- Two height options available: 4' and 6'
- Minimum Breaking Strength: 3,600 lbs. (1633 kg)

### FALL ARREST POINT(S) :

- Captive eye

### ITEM WEIGHT :

- See chart below



\*SRL sold separately

| USER WEIGHT CAPACITY |                          |
|----------------------|--------------------------|
| ANSI                 | 130-310 lbs. (59-141 kg) |
| OSHA                 | Up to 420 lbs. (191 kg)  |

| SIZE(S)   |                                     |
|-----------|-------------------------------------|
| 022-12146 | 4 ft. (1.2 m) / 41.0 lbs. (18.6 kg) |
| 022-12147 | 6 ft. (1.8 m) / 48.6 lbs. (22.0 kg) |
|           |                                     |
|           |                                     |
|           |                                     |
|           |                                     |
|           |                                     |

| STANDARD COMPLIANT WITH |                    |
|-------------------------|--------------------|
| ANSI                    | N/A                |
| OSHA                    | 1926.502, 1910.140 |

| COMPONENT         | MATERIAL SPECIFICATION        |
|-------------------|-------------------------------|
| Head Unit         | Powder coated stainless steel |
| Post              | Galvanized steel              |
| Extension bracket | Galvanized steel              |
| U-Bolts/Nuts      | Zinc plated steel             |
| Captive eye       | Zinc plated steel             |
|                   |                               |
|                   |                               |