



022-6061 through 022-6065

Rescue/Descent System

FEATURES :

- Lightweight aluminum bidirectional descent device with swivel carabiner
- Device includes lifting wheel for rescue capability
- Assisted or unassisted descent capability
- Dual brake pad heat-dissipating housing with 1:8.2 gear ratio
- 2 Integral rope belays
- Built-in rope lock
- Rated for use by 1 or 2 persons
- Low stretch ANSI compliant rope with captive eye and steel carabiner
- FS810-3 - 3' reinforced cross arm strap anchor
- 018-9001 - 36" rope protector
- 022-6073 - Rescue Pole Kit with 4-18' telescoping pole, tool attachment and tether, pole head bracket
- 022-6071 - Aluminum Carabiner
- 022-6070 - Web connector strap
- 022-9087 - Rescue Gear bag
- Max descent length: 525' (160 m)
- Max Lifting Capacity: 85 lbs. - 15', 310 lbs. - 10', 420 lbs. - 5', 620 lbs. - 3'
- Anchor strength requirement: 3,100 lbs (1400 kg)

ITEM WEIGHT :

- Weight varies per length



USER WEIGHT CAPACITY

ANSI	1 person: 110-310 lbs. (50-141 kg)
OSHA	2 person: Up to 620 lbs. (281 kg)

STANDARD COMPLIANT WITH

ANSI	Z359.4-2013
OSHA	1910.140, 1926.502

SIZE(S)

022-6061	150 Feet (46 m)	25.1 lbs. (11.4 kg)
022-6062	200 Feet (61 m)	27.1 lbs. (12.3 kg)
022-6063	300 Feet (91 m)	31.1 lbs. (14.1 kg)
022-6064	400 Feet (122 m)	35.1 lbs. (15.9 kg)
022-6065	500 Feet (152 m)	39.1 lbs. (17.7 kg)

MATERIAL SPECIFICATION

Descent device	Aluminum, stainless steel, nylon
Rope	9.3 mm nylon/polyester kernmantle
Rope protector	Water repellent tarpaulin
Cross arm strap	Polyester, zinc plated alloy steel
Gear Bag/Pole bag	Water repellent tarpaulin
Swivel carabiner	Zinc plated steel
Rope carabiner	Yellow chromate plated steel
Rescue Pole	Aluminum
Pole Head Bracket	Stainless steel
Pick-off carabiner	Aluminum
Web Connector	Dyneema® webbing
Tool Attachment	Polyester webbing, steel D-ring
Tool Tether	Elasticated polyester webbing, aluminum carabiners