



## **BELMONT SAFETY HATCH SYSTEM**

### **ELEVATED LADDER SAFETY**

Climbing a ladder is dangerous. Opening or closing a roof hatch while climbing is even more dangerous.

We have the solution.

- **Operate the roof hatch from the safety of the ground** – and keep your hands free for climbing.
- **An innovative built-in handle extends** to provide added safety between the ladder and roof – ensuring safe, smooth transitions.

### **SAFE ROOFTOP ACCESS WHEN USING A HATCH FROM A FIXED LADDER**

- Commercial Maintenance
- Industrial Buildings
- Manufacturing Plants
- Healthcare Facilities
- Data Centers
- Warehouses
- Retail Operations



# USE OF A LADDER ON THE JOB IS ONE OF THE MOST COMMON ACTIVITIES PRECEDING A FALL.

(2023 The Center for Construction Research and Training)

For use on hatches from 30" square to 36" square

Patent # US 11,293,226 B2

## BELMONT SAFETY HATCH SYSTEM

Safe rooftop access when using a hatch from a fixed ladder

### ▶ SMOOTH TRANSITIONS

Built in safety handle automatically extends at top for smooth transition from ladder to roof

### ▶ SAFER CLIMBING

Open and close hatch from the ground, allowing worker to maintain three points of contact while on ladder

### ▶ ADDED SECURITY

Lock and unlock roof hatch without having to climb on ladder

### ▶ HATCH LOCK

Toggle prevents accidental closure and can be secured with padlock

### ▶ SIMPLE TO USE

Just turn the hand crank to open and close system

### ▶ VERSATILE

Bolt-on system easily attaches with multiple bracket options to most fixed indoor ladders (10' to 34')

### KEY SPECS:

Materials: Powder coated steel, zinc plated steel fasteners

System Capacity: 600 lbs. (272.2 kg)

### TOOLS REQUIRED FOR INSTALLATION:

- » Fall protection
- » 7/16" wrench or socket
- » 9/16" wrench or socket
- » 3/4" wrench
- » 5/16" nut driver
- » Saw
- » Drill (Rivet drill bit attachment included)
- » All required fasteners included

023-12154	10' to 20'	Flat Brackets
023-12155	20' to 27'	Flat Brackets
023-12156	27' to 34'	Flat Brackets
023-12157	10' to 20'	Front Mount Brackets
023-12158	20' to 27'	Front Mount Brackets
023-12159	27' to 34'	Front Mount Brackets
023-12160	10' to 20'	Round Brackets
023-12161	20' to 27'	Round Brackets
023-12162	27' to 34'	Round Brackets
023-12163	Replacement Flat/Square Backing Plate Set	
023-12164	Replacement Front Mount Backing Plate Set	
023-12165	Replacement Round Backing Plate Set	



225 Wilshire Avenue SW, Concord NC 28025 • 800-230-0319 • safewaze.com

