2-in-1 Hand Riveter

Economy Hand Riveter



One hand operation with normal squeezing action provides enough pulling power to set all popular size rivets. 2-in-1 adjustment features a single long stroke for most hand riveting applications and a short "ratchet action" power stroke for setting larger diameter rivets. Outside jaw-grip adjustment wheel opens and closes jaws with fingertip ease to fit any size mandrel and to obtain maximum stroke efficiency.

Professional slim nose allows 2-in-1 to go where other hand riveters cannot. Ideal for reaching into corners and recessed areas. Three nosepieces 1/8, 5/32, and 3/16 in., included with tool. Nosepieces are stored in handle. Heavy duty all steel construction insures long life and minimum wear. Polished finish, nickel-chrome plated. Red vinyl cushion grip and hand stop.



CR18

Lightweight, compact size and slim nose projection allows this riveter to go wherever the work is. Four rivet nosepieces: 3/32, 1/8, 5/32 and 3/16 in. store in handle. Ideally suited for blind riveting applications in aluminum windows, gutter and downspout. Not for use with 5/32 in. or 3/16 in. steel rivets (steel rivets larger than 3.2 mm). Spring return handles and comfortable contour grip make operation fast and easy. Just open handles and insert rivet into tool until flange touches nosepiece. Squeeze handles slightly to allow jaws to grip rivet mandrel. Insert rivet into pre-drilled work to be fastened and squeeze handles until mandrel snaps. Release grip on handles and mandrel will drop out front end of tool when tilted. Rugged steel construction with black paint finish and comfortable vinyl grip. Secure handle latch makes this tool easy to fit in pouch or pocket.





Metal Cutting Saw Blade

Cool Clean Cuts in metal roofing & metal building panels







Standing Seam Metal Roofing

MCCB7

Metal Building Panels

Specially formulated, tough c-6 carbide tipped blade fits all popular brands of portable circular saws. Lasts up to 30 times longer than abrasive disks for cutting unhardened ferrous metal. Makes true, flat cuts in standing seam metal roofing and metal building panels without burning paint or protective coatings. Also makes clean cuts in metal studs, light angle iron and thin walled pipe.

| Catalog | Dan mindian | Capacities | | | | | Length | Net Wt. |
|---|-------------------------|---|------|-------|------------------------|----------|----------|----------|
| Number | Description | in. (mm) | | | | | in. (mm) | oz. (g) |
| 2IN1 | 2-in-1 Hand Riveter | 1/8 thru- 3/16 (3.18 - 4.8) steel mandrel / 1/8 thru- 5/32 (3.18 - 4.0) stainless steel mandrel | | | | | 8 (203) | 20 (567) |
| CR18 | Economy Hand Riveter | 3/32 thru 1/8 (2.4 - 3.2) steel rivets | | | | | 8 (203) | 22 (624) |
| Replacement Accessories and Parts for 2-in-1 Hand Riveter | | | | | | | | |
| ER41 | Jaws | | | | | | | |
| ER44 | 3/16 in. nosepiece | | | | | | | |
| ER45 | 1/8 in. nosepiece | | | | | | | |
| ER46 | 5/32 in. nosepiece | | | | | | | |
| HR37 | Adjustment Rod assembly | | | | | | | |
| | | | | | | | | |
| Catalog | | Diameter | | | Capacity in Mild Steel | Arbor | | |
| Number | Description | in. (mm) | RPM | Teeth | gauge (mm) | in. (mm) | | |
| МССВ7 | Metal Cutting Saw Blade | 7-1/4 (184) | 5800 | 56 | 16 (1.52) | 5/8 (16) | | |