

# PRODUCT SPECIFICATIONS

## Contractor 1-D Full Body Harness

## #70163X

### Features

- Single back d-ring for fall arrest
- 5-point adjustability
- 9-position tongue buckle leg straps
- 1 lanyard keeper
- Size: 3X Large

### Material Specifications

- Webbing:** *Polyester; Min. 5,000 lbs. tensile strength*
- D-Rings:** *Alloy Steel; Min. 5,000 lbs. tensile strength*
- Buckles/Adjusters:** *Alloy Steel; Min. 3,375 lbs. tensile strength*

### Performance Specifications

- Tensile Strength:** *Min. 5,000 lbs.*
- Max. Capacity:** *425 lbs.*  
*To maintain ANSI Z359 compliance, limit total user weight to 310lbs*

### Relevant Standards

- OSHA:** *CFR1926.502, CFR1910.66*
- ANSI:** *A10.32-2004, Z359.1-2007, Z359.12-2009*

### Warnings

- Read, understand and follow all labels and instructions prior to use.
- Inspect before each use.
- Remove from service if there is evidence of damage or excessive wear.
- Never attach a Shock Absorbing Lanyard to the front or side D-Rings.



EQUIPMENT UNDERGO THOROUGH TRAINING, AND THAT ALL WARNINGS AND INSTRUCTIONS PROVIDED WITH THESE PRODUCTS BE THOROUGHLY READ UNDERSTOOD PRIOR TO USE. FAILURE TO READ AND FOLLOW ALL PRODUCT WARNINGS AND INSTRUCTIONS COULD RESULT IN SERIOUS INJURY OR DEATH.

