

# PRODUCT SPECIFICATIONS

## 7073

### Contractor Construction Belted Harness

Contractor harnesses are serviceable entry-level fall protection essentials for infrequent to daily use in Fall Arrest, Work Positioning and Climbing applications. Available in 1 and 3 D-ring Non-belted, 3 D-ring Construction Belted and 2 or 4 D-ring Crossover models to cover requisite needs.

#### Features

- Dorsal and Hip D-rings for Fall Arrest and Work Positioning applications
- Mating Buckle chest and torso adjusters
- 9-position Tongue Buckle leg and belt closures
- 2 Lanyard parking keepers
- Heavy-duty belt with waist support positioning pad and adjustable shoulder pads
- Sizes small up to 3X

MATERIAL SPECIFICATIONS	
<b>Webbing:</b>	Polyester, 5,000 lbs. Min. Static Strength
<b>D-ring:</b>	Plated Alloy Steel, 5,000 lbs. Min. Static Strength
<b>Buckles/Adjusters:</b>	Plated Alloy Steel, 3,375 lbs. Min. Static Strength

ANSI PERFORMANCE SPECIFICATIONS	
<b>Static Strength:</b>	3,600 lbs. Min.
<b>ANSI User Capacity:</b>	310 lbs. Max.
<b>OSHA User Capacity:</b>	425 lbs. Max.

PART #	SIZE
<b>7073SM</b>	Dual-size, Sm/Med
<b>7073LX</b>	Dual-size, Lrg/XL
<b>70732X</b>	2XL
<b>70733X</b>	3XL

RELEVANT STANDARDS	
<b>ANSI:</b>	Z359.11-2014
<b>OSHA:</b>	1926.502 and 1910.66



#### WARNINGS

- Read, understand and follow all labels and instructions prior to use.
- Inspect before each use.
- Remove from service if there is evidence of damage or excessive wear.
- Never connect an Energy Absorbing Lanyard to Hip D-ring.

**Warning:** All Fall Protection equipment should only be used after reading and understanding the manufacturer's instructions and proper training on the product. Failure to receive proper training and following the manufacturer's instructions could result in serious injury or death.