

PRODUCT SPECIFICATIONS

Permanent Truss Anchor Kit

#7429SSK

Features

- Permanent Roof Truss Anchor
- For residential and commercial pitched wood roof applications
- May be installed during and after construction
- Connector Hole: 11/16"
- Anchor Height: 10-3/4"
- Nail Holes: 3/16"
- Includes (12) 1-1/2" stainless steel truss nails
- Flange: 10" x 10"
- Protective Cap: 6-3/4" with 15" zip-tie

Material Specifications

Anchor *304 Stainless steel*

Fasteners: *1½" Stainless Steel*

Flange: *EPDM*

Protective Cap: *Polypropylene*

Performance Specifications

Tensile Strength: *Min. 3,6000 lbs.*

Max. Capacity: *425 lbs.*

Relevant Standards

OSHA: *CFR1926.502, CFR1910.66*

Warnings

- Read, understand and follow all labels and instructions prior to use.
- Inspect before each use.
- Remove from service if there is evidence of damage or excessive wear.



FallTech 1306 S. Alameda St. Compton, CA 90221 Tele: 323-752-0066 www.falltech.com

WARNING: THIS SPECIFICATION SHEET PROVIDES AN OVERVIEW OF PRODUCTS AVAILABLE FROM FALLTECH. CARE HAS BEEN TAKEN TO ASSURE THE ACCURACY OF THE INFORMATION. IT DOES NOT PROVIDE IMPORTANT PRODUCT WARNINGS AND INSTRUCTIONS. FALLTECH RECOMMENDS ALL USERS OF FALL PROTECTION EQUIPMENT UNDERGO THOROUGH TRAINING, AND THAT ALL WARNINGS AND INSTRUCTIONS PROVIDED WITH THESE PRODUCTS BE THOROUGHLY READ UNDERSTOOD PRIOR TO USE. FAILURE TO READ AND FOLLOW ALL PRODUCT WARNINGS AND INSTRUCTIONS COULD RESULT IN SERIOUS INJURY OR DEATH.