

PRODUCT SPECIFICATIONS

Single Use Roof Anchor - 10 Pack

#744410

Features

- For temporary anchorage on a roof structure.
- Mounts with (8) 3-1/2" 16d VC sinkers (included)
- Alloy steel construction
- Meets the requirements of OSHA 1926

Material Specifications

Roof Anchor: *Alloy Steel; Min 3600lbs tensile strength*

Performance Specifications

Tensile Strength: *Min. 3,600 lbs.*

Max. Capacity: *310 lbs.*

Relevant Standards

OSHA: *CFR1926.502, CFR1910.66*

Warnings

- Read, understand and follow all labels and instructions prior to use.
- Inspect before each use.
- Remove from service if there is evidence of damage or excessive wear.



FallTech 1306 S. Alameda St. Compton, CA 90221 Tele: 323-752-0066 www.falltech.com

WARNING: THIS SPECIFICATION SHEET PROVIDES AN OVERVIEW OF PRODUCTS AVAILABLE FROM FALLTECH. CARE HAS BEEN TAKEN TO ASSURE THE ACCURACY OF THE INFORMATION. IT DOES NOT PROVIDE IMPORTANT PRODUCT WARNINGS AND INSTRUCTIONS. FALLTECH RECOMMENDS ALL USERS OF FALL PROTECTION EQUIPMENT UNDERGO THOROUGH TRAINING, AND THAT ALL WARNINGS AND INSTRUCTIONS PROVIDED WITH THESE PRODUCTS BE THOROUGHLY READ UNDERSTOOD PRIOR TO USE. FAILURE TO READ AND FOLLOW ALL PRODUCT WARNINGS AND INSTRUCTIONS COULD RESULT IN SERIOUS INJURY OR DEATH.