PRODUCT SPECIFICATIONS

9' WrapTech Mini Web Self-Retracting Device

Features

- · 9' Single Leg SRD
- \cdot 3' abrasion-resistant jacketed tie-back leg
- $\cdot\,$ Compact and impact resistant nylon housing
- · Integral shock absorber provides visual fall event indication
- · Integral Swivel eye Reduces twisting
- · 5k Tie-back Carabiner on leg end
- · Steel Carabiner on housing-end

Material Specifications

Webbing:	100% Dyneema, 4,500lbs min
Energy Absorber	Polyester
Swivel Eye:	Alloy Steel, 5/8" hole diameter
SRD Housing:	Nylon 6/6
Main Shaft:	Alloy steel
Pawls:	Stainless steel
Leg-end Connector:	Alloy Steel, 5,000lbs min. Static
	strength with 5,000lbs gate
Housing Connector:	Alloy Steel, 5,000lbs min. Static
	strength with 3,600lbs gate

Performance Specifications

Static Strength: User Capacity: Max. Arrest Distance: Average Arrest Force: Max. Arrest Force: ANSI SRD Class: 3,000lbs min. 310 lbs. max. 54" 1,125lbs or less 1,800 lbs Class B

Relevant Standards

OSHA:

Warnings

· Read, understand and follow all labels and instructions prior to use.

CFR1926.502, CFR1910.66

- Inspect before each use.
- Remove from service if there is evidence of damage or excessive wear.
- · Remove from service if there is any signs of activation.

FallTech 1306 S. Alameda St. Compton, CA 90221 Tele: 323-752-0066 www.falltech.com

WARNING: THIS SPECIFICATION SHEET PROVIDES AN OVERVIEW OF PRODUCTS AVAILABLE FROM FALLTECH. CARE HAS BEEN TAKEN TO ASSURE THE ACCURACY OF THE INFORMATION. IT DOES NOT PROVIDE IMPORTANT PRODUCT WARNINGS AND INSTRUCTIONS. FALLTECH RECOMMENDS ALL USERS OF FALL PROTECTION EQUIPMENT UNDERGO THOROUGH TRAINING, AND THAT ALL WARNINGS AND INSTRUCTIONS PROVIDED WITH THESE PRODUCTS BE THOROUGHLY READ UNDERSTOOD PRIOR TO USE. FAILURE TO READ AND FOLLOW ALL PRODUCT WARNINGS AND INSTRUCTIONS COULD RESULT IN SERIOUS INJURY OR DEATH.





Fall Protection. Precision Engineered.