

PRODUCT SPECIFICATIONS

50' Vertical Lifeline

8150

Features

- Anchor-end snap hook and trailing end braided eye.
- 5/8" polyester rope has a tensile strength of 8,500 lbs.
- Superior resistance to abrasion and UV light.
- Superior hockle resistance.
- Five-tuck splice for superior strength and safety.
- Exclusive steel thimble resist wear and extend the life of the line.
- Protective PVC shrink tubing protects the spliced ends.

Material Specifications

Rope:	<i>5/8" Polyester; Min. 8,500 lbs. tensile strength</i>
Connectors:	<i>Alloy Steel; Min. 5,000 lbs. tensile strength</i>
Thimble:	<i>Alloy Steel</i>
Connector Gates:	<i>Alloy Steel; Min. 3,600 lbs. front and side load</i>

Performance Specifications

Tensile Strength:	<i>Min. 5,000 lbs.</i>
Max. Capacity:	<i>425 lbs.</i>
	<i>To maintain ANSI Z359 compliance, limit total user weight to 310lbs</i>

Relevant Standards

OSHA:	<i>CFR1926.502, CFR1910.66</i>
ANSI:	<i>A10.32-2004</i>
	<i>Z359.1-2007</i>

Warnings

- Read, understand and follow all labels and instructions prior to use.
- Inspect before each use.
- Remove from service if there is evidence of damage or excessive wear.



FallTech 1306 S. Alameda St. Compton, CA 90221 Tele: 323-752-0066 www.falltech.com

WARNING: THIS SPECIFICATION SHEET PROVIDES AN OVERVIEW OF PRODUCTS AVAILABLE FROM FALLTECH. CARE HAS BEEN TAKEN TO ASSURE THE ACCURACY OF THE INFORMATION. IT DOES NOT PROVIDE IMPORTANT PRODUCT WARNINGS AND INSTRUCTIONS. FALLTECH RECOMMENDS ALL USERS OF FALL PROTECTION EQUIPMENT UNDERGO THOROUGH TRAINING, AND THAT ALL WARNINGS AND INSTRUCTIONS PROVIDED WITH THESE PRODUCTS BE THOROUGHLY READ UNDERSTOOD PRIOR TO USE. FAILURE TO READ AND FOLLOW ALL PRODUCT WARNINGS AND INSTRUCTIONS COULD RESULT IN SERIOUS INJURY OR DEATH.