

PRODUCT SPECIFICATIONS

100' Vertical Lifeline

8200

Features

- Anchor-end snap hook and trailing end back braided eye
- 5/8" polyester rope
- Five-tuck splice
- Steel thimble
- Protective PVC shrink tubing

Material Specifications

- Rope:** *5/8" Polyester; Min. 5,600 lbs. tensile strength*
- Connectors:** *Alloy Steel; Min. 5,000 lbs. tensile strength*
- Thimble:** *Alloy Steel*
- Connector Gates:** *Alloy Steel; Min. 3,600 lbs. front and side load*

Performance Specifications

- Tensile Strength:** *Min. 5,600 lbs.*
- Max. Capacity:** *310 lbs.*

Relevant Standards

- OSHA:** *CFR1926.502, CFR1910.66*
- ANSI:** *ANSI Z359.1-2007, A10.32-2004*

Warnings

- Read, understand and follow all labels and instructions prior to use.
- Inspect before each use.
- Remove from service if there is evidence of damage or excessive wear.



FallTech 1306 S. Alameda St. Compton, CA 90221 Tele: 323-752-0066 www.falltech.com

WARNING: THIS SPECIFICATION SHEET PROVIDES AN OVERVIEW OF PRODUCTS AVAILABLE FROM FALLTECH. CARE HAS BEEN TAKEN TO ASSURE THE ACCURACY OF THE INFORMATION. IT DOES NOT PROVIDE IMPORTANT PRODUCT WARNINGS AND INSTRUCTIONS. FALLTECH RECOMMENDS ALL USERS OF FALL PROTECTION EQUIPMENT UNDERGO THOROUGH TRAINING, AND THAT ALL WARNINGS AND INSTRUCTIONS PROVIDED WITH THESE PRODUCTS BE THOROUGHLY READ UNDERSTOOD PRIOR TO USE. FAILURE TO READ AND FOLLOW ALL PRODUCT WARNINGS AND INSTRUCTIONS COULD RESULT IN SERIOUS INJURY OR DEATH.