PRODUCT SPECIFICATIONS



DuraTech 6' Web Self-Retracting Device

82706SB1

Features

- · Single-leg SRD
- · 6' working length
- · Glass reinforced polycarbonate housing
- · Impact-resistant over molded side-walls
- · Steel Snap Hook
- · Steel Carabiner w/Captive Pin
- · Integral Swivel eye Reduces twisting

Material Specifications

Webbing: 80% Dyneema, 20% Polyester;

Swivel eye: Aluminum
Spring: Stainless steel

SRD Housing: Glass reinforced polycarbonate

Main Shaft:Alloy steelPawls:Stainless steelConnectorsAlloy Steel

Performance Specifications

Tensile Strength: Min. 3,000 lbs tensile strength

Max. Capacity: 310 lbs. Max. Deceleration distance: 28"

Average Arrest Force: Less than 900 lbs.

Max. Arrest Force: 1,800 lbs
Class of SRD: Class B

Connectors: 3,600lb min. gate strength

Relevant Standards

OSHA: *CFR1926.502, CFR1910.66*ANSI: *ANSI Z359.14-2012*

Warnings

- · Read, understand and follow all labels and instructions prior to use.
- · Inspect before each use.
- · Remove from service if there is evidence of damage or excessive wear.
- \cdot Remove from service if there is any signs of activation.
- · For use up to Max 2' below the user's dorsal D-ring.



FallTech 1306 S. Alameda St. Compton, CA 90221 Tele: 323-752-0066 www.falltech.com