

PRODUCT SPECIFICATIONS

DuraTech 6' Web Self-Retracting Device

82706TB1

Features

- Twin-leg SRD for 100% Tie-Off
- 6' working length.
- Glass reinforced polycarbonate housing
- Impact-resistant over molded side-walls bumpers
- Steel Snap Hooks
- Carabiner with Alignment Clip
- Integral Swivel Eye

Material Specifications

Webbing:	<i>80% Dyneema, 20% Polyester;</i>
Swivel Eye:	<i>Aluminum</i>
Spring:	<i>Stainless steel</i>
SRD Housing:	<i>Glass reinforced polycarbonate</i>
Main Shaft:	<i>Alloy steel</i>
Pawls:	<i>Stainless steel</i>
Connectors	<i>Steel Alloy</i>

Performance Specifications

Tensile Strength:	<i>Min. 3,000 lbs tensile strength</i>
Max. Capacity:	<i>310 lbs.</i>
Max. Deceleration distance:	<i>28"</i>
Average Arrest Force:	<i>Less than 900 lbs.</i>
Max. Arrest Force:	<i>1,800 lbs</i>
Class of SRD:	<i>Class B</i>
Connectors:	<i>3,600lb min. gate strength</i>

Relevant Standards

OSHA:	<i>CFR1926.502, CFR1910.66</i>
ANSI:	<i>ANSI Z359.14-2012</i>

Warnings

- Read, understand and follow all labels and instructions prior to use.
- Inspect before each use.
- Remove from service if there is evidence of damage or excessive wear.
- Remove from service if there is any signs of activation.
- For use up to Max 2' below the user's dorsal D-ring.



FallTech 1306 S. Alameda St. Compton, CA 90221 Tele: 323-752-0066 www.falltech.com

WARNING: THIS SPECIFICATION SHEET PROVIDES AN OVERVIEW OF PRODUCTS AVAILABLE FROM FALLTECH. CARE HAS BEEN TAKEN TO ASSURE THE ACCURACY OF THE INFORMATION. IT DOES NOT PROVIDE IMPORTANT PRODUCT WARNINGS AND INSTRUCTIONS. FALLTECH RECOMMENDS ALL USERS OF FALL PROTECTION EQUIPMENT UNDERGO THOROUGH TRAINING, AND THAT ALL WARNINGS AND INSTRUCTIONS PROVIDED WITH THESE PRODUCTS BE THOROUGHLY READ UNDERSTOOD PRIOR TO USE. FAILURE TO READ AND FOLLOW ALL PRODUCT WARNINGS AND INSTRUCTIONS COULD RESULT IN SERIOUS INJURY OR DEATH.