

83208TPO

8' CTX™ Cable Class 2 Leading Edge Personal SRL-P, Twin-leg with Steel Mini Rebar Hooks

Features :

- Ergonomic design keeps retractable units elevated on the back to reduce fatigue and maximize productivity
- Energy absorber cover includes comprehensive fall clearance charts and tables
- Internal mechanism design minimizes unintentional lockups to keep you moving freely and productively
- Suitable for below D-ring tie-off up to five feet and leading edge exposures and hazards, including steel and precast concrete
- Rated for workers weighing up to 310 pounds, including clothes, tools, gear, etc.
- Complies with ANSI Z359.14-2021 Class 2 SRL-P. [Learn more and download White Paper](#)



Material Specifications	
Cable	3/16" galvanized steel; 3,600 lb min. static strength
Energy Absorber	Polyester tear-away
Anchorage Connector	Plated alloy steel; 5,000 lb min. static strength with 3,600 lb gate strength
Dorsal Connector	Aluminum alloy; 3,600 lb min.

Performance Specifications	
Static Strength	3,600 lb min.
ANSI SRL Class/Type	Class 2 SRL-P
Avg. Arrest Force	1,350 lb max.
Max. Arrest Force	1,800 lb
Max. Arrest Distance	42"
ANSI User Capacity	130 to 310 lb max.
OSHA User Capacity	130 to 310 lb max.

Compliant With:	
ANSI	Z359.14-2021
OSHA	1926.502 and 1910.66