

**83208TP1**

**8' CTX™ Cable Class 2 Leading Edge Personal SRL-P, Twin-leg with Steel Snap Hooks**

**Features :**

- Ergonomic design keeps retractable units elevated on the back to reduce fatigue and maximize productivity
- Energy absorber cover includes comprehensive fall clearance charts and tables
- Internal mechanism design minimizes unintentional lockups to keep you moving freely and productively
- Suitable for below D-ring tie-off up to five feet and leading edge exposures and hazards, including steel and precast concrete
- Rated for workers weighing up to 310 pounds, including clothes, tools, gear, etc.
- Complies with ANSI Z359.14-2021 Class 2 SRL-P. [Learn more and download White Paper](#)



Material Specifications	
<b>Cable</b>	3/16" galvanized steel; 3,600 lb min. static strength
<b>Energy Absorber</b>	Polyester tear-away
<b>Anchorage Connector</b>	Plated alloy steel; 5,000 lb min. static strength with 3,600 lb gate strength
<b>Dorsal Connector</b>	Aluminum alloy; 3,600 lb min.

Performance Specifications	
<b>Static Strength</b>	3,600 lb min.
<b>ANSI SRL Class/Type</b>	Class 2 SRL-P
<b>Avg. Arrest Force</b>	1,350 lb max.
<b>Max. Arrest Force</b>	1,800 lb
<b>Max. Arrest Distance</b>	42"
<b>ANSI User Capacity</b>	130 to 310 lb max.
<b>OSHA User Capacity</b>	130 to 310 lb max.

Compliant With:	
<b>ANSI</b>	Z359.14-2021
<b>OSHA</b>	1926.502 and 1910.66