

# PRODUCT SPECIFICATIONS

## Leading Edge Lanyards



8354LE



8354LE3



8354LEY



8354LEY3



8354LEY3D



8354LEYA



8354LE3YA

### MATERIALS SPECIFICATIONS

<b>¼" Galvanized Steel Cable</b>	5,000 lbs.
<b>Connectors:</b>	5,000 Minimum with 3,600 lbs. Gate Strength
<b>D-ring:</b>	5,000 lbs.

### PERFORMANCE SPECIFICATIONS

<b>Minimum Static Strength:</b>	5,000 lbs.
<b>ANSI Lanyard Class</b>	12' Free Fall
<b>Maximum Arrest Distance:</b>	60"
<b>Average Arrest Force:</b>	1,350 lbs.
<b>Maximum Arrest Force:</b>	1,800 lbs.

### RELEVANT STANDARDS

<b>ANSI</b>	ANSI Z359.13-2013
<b>OSHA</b>	1926.502, 1910.66

### WARNINGS

- Read, understand and follow all labels and instructions prior to use.
- Inspect before each use.
- Remove from service if there is evidence of damage or excessive wear.
- Remove from service if there is any sign of activation.

**Warning:** All Fall Protection equipment should only be used after reading and understanding the manufacturer's instructions and proper training on the product. Failure to receive proper training and follow the manufacturer's instructions could result in serious injury or death.