

# PRODUCT SPECIFICATIONS

## Fall Arrester and Shock Absorbing Lanyard

## #8368

### Features

- For use on 5/8" Polyester or Copolymer rope for fall arrest.
- Integral energy absorber with fall arrester set in 3' length.
- Self-tracking design provides ease of vertical movement.
- Double-locking snap hook at the attachment end.

### Material Specifications

<b>Webbing:</b>	<i>Polyester; Min. 5,000 lbs. tensile strength</i>
<b>Energy Absorber:</b>	<i>Polyester; activation greater than 450 lbs.</i>
<b>Connectors:</b>	<i>Alloy Steel; Min. 5,000 lbs. tensile strength</i>
<b>Connector Gates:</b>	<i>Alloy Steel; Min. 3,600 lbs. front load and side load.</i>

### Performance Specifications

<b>Tensile Strength:</b>	<i>Min. 5,000 lbs.</i>
<b>Max. Capacity:</b>	<i>310 lbs.</i>
<b>Max. Freefall:</b>	<i>6 feet</i>
<b>Max. Arrest Force:</b>	<i>Less than 900 lbs.</i>
<b>Max. Elongation:</b>	<i>48 inches</i>

### Relevant Standards

<b>OSHA:</b>	<i>CFR1926.502, CFR1910.66</i>
<b>ANSI:</b>	<i>Z359.13.2009</i>

### Warnings

- Read, understand and follow all labels and instructions prior to use.
- Inspect before each use.
- Remove from service if there is evidence of damage or excessive wear.
- Remove from service if there are any signs of activation.
- Never attach a Shock Absorbing Lanyard to the front or side D-rings.



FallTech 1306 S. Alameda St. Compton, CA 90221 Tele: 323-752-0066 www.falltech.com

WARNING: THIS SPECIFICATION SHEET PROVIDES AN OVERVIEW OF PRODUCTS AVAILABLE FROM FALLTECH. CARE HAS BEEN TAKEN TO ASSURE THE ACCURACY OF THE INFORMATION. IT DOES NOT PROVIDE IMPORTANT PRODUCT WARNINGS AND INSTRUCTIONS. FALLTECH RECOMMENDS ALL USERS OF FALL PROTECTION EQUIPMENT UNDERGO THOROUGH TRAINING, AND THAT ALL WARNINGS AND INSTRUCTIONS PROVIDED WITH THESE PRODUCTS BE THOROUGHLY READ UNDERSTOOD PRIOR TO USE. FAILURE TO READ AND FOLLOW ALL PRODUCT WARNINGS AND INSTRUCTIONS COULD RESULT IN SERIOUS INJURY OR DEATH.