



SL Series Cap Style

STANDARDS

ANSI Z89.1 • CSA Z94.1 •

Low-profile design // High density polyethylene materials // Rain trough // Universal accessory slots // Available with 4- and 6-point nylon suspensions — snap lock and ratchet styles // Suspensions adjust from 6.5 - 8 head size // Passes for reverse orientation and low temperature (LT) // Meets Class E, G, and C // Hi-vis colors have been tested for the HV mark // Custom imprinting available

4-Point Ratchet | 13 Variations

- HP14110 ● White
- HP14111 • Blac
- HP14112 •• Gray
- HP14120 ●● Red
- HP14130 ●● Yellow
- HP14131 ●● Hi-vis Lime
- HP14135 ●● Green
- HP14140 ●● Orange
- HP14141 ● Hi-vis Orange
- HP14160 ●● Blue
- HP14162 Light Blue
- HP14165 ●● Dark Blue
- HP14170 ●● Pink

6-Point Ratchet | 7 Variations

- HP16110 White
- HP16120 Red
- HP16130 Yellow
- UD4C42F a
 - HP16135 Green
- HP16140 ●
- HP16141 Hi-vis Orange
- HP16160 E

10111 111 111

Orange

4-Point Snap Lock | 8 Variations

- HP14010 White
- HP14020 Red
- 111 14020 Ned
- HP14030 Yellow
- HP14031 Hi-vis Lime
- HP14035 Green
- HP14040 Orange
- UP44060 a Phys
- HP14060 Blue
 - HP14062 Light Blue

6-Point Snap Lock | 5 Variations

- HP16010 White
- HP16020 Red
- HP16030 Yellow
- HP16035 Green
- HP16040 Orange





STANDARDS

ANSI Z89.1, Type 1, Class C, G, and E CSA Z94.1

SPECS

HAT

Shell High density polyethylene

SUSPENSION

Strap Nylon

WEIGHTS AND MEASUREMENTS

Weight 360 grams / 12.7 oz General Dimensions 5.75" H x 11" L x 9" W

Headband Sizes 6.5-8

FEATURES

Accessory slots
Chin strap attachment
Replacement suspension
Reverse donning
Rain trough



Maximum service life of 5 years (shell) & 1 year (suspension) from the time of first use

Never alter or modify the shell or suspension system

Inspect the hard hat each time before use and replace if there is any sign of damage $\,$

Replace hard hat after it receives a considerable impact

Accessories such as liners have not been tested to the requirement of this standard

Clean only with mild soap and lukewarm water

Store hard hat in a clean, dry place that is out of direct sunlight

Do not use paints, chemicals, adhesives, gasoline or similar substances on the hard hat

Labels are acceptable if they do not affect a hard hat's protective rating or make it

difficult to find damage

