



PYRAMEX
Perform At Your Peak

PMXSLIM® ANSI CE AUS



ADJUSTABLE
NOSEPIECE



CO-INJECTED
TEMPLES

Slim fit for smaller facial features

Soft, adjustable nosepiece

Co-injected temple design includes soft rubber tips for a non-slip fit

Part No.	Black Temples
ESB7110S ●●	Clear
ESB7110ST ●●●	AF Clear H2X
ESB7120S ●●	Gray
ESB7120ST ●●●	AF Gray H2X
ESB7130S ●●	Amber
ESB7138S ●●●	Sandstone Bronze
ESB7180S ●●●	I/O Mirror



There's more to see at
PYRAMEXSAFETY.COM

(P) +44 (0) 1635 254220 | (E) info@pyramexeurope.com

All safety eyewear meets ANSI Z87.1+ standards (●) and provide 99% protection from harmful UV rays. All lenses are hard coated polycarbonate scratch-resistant unless otherwise noted. Some options meet European [EN166] (●) or Australian [AS/NZS 1337] (●) standards. For specific lens options visit our website or contact your sales representative.

PMXSLIM®

General Specifications

Weight: 25 gm
 PD: 68 mm
 Bridge: 14.5 mm
 Lens base: 10 curve
 Lens size diagonal: 137.7 mm
 Lens size vertical: 45 mm
 Lens thickness: 2.3 mm
 Overall length (lens - tip): 170 mm
 Overall width (hinge - hinge): 129 mm
 Closest point between temple tips: 86 mm
 Closest point between lens: 9 mm

Materials

Lens: polycarbonate
 Frame: polycarbonate
 Temples: polycarbonate & thermoplastic elastomers (TPE)
 Hinge: polycarbonate
 Screw: stainless steel
 Side shields: polycarbonate
 Nosepiece: polyvinyl chloride (PVC)

Part No.	Lens Markings	Frame Markings
ESB7110S	2 C - 1.2 P 1 F CE	CE P EN166 F
ESB7110ST	2 C - 1.2 P 1 F N CE	CE P EN166 F
ESB7120S	5 -2.5 P 1 F CE	CE P EN166 F
ESB7120ST	5 -2.5 P 1 F N CE	CE P EN166 F
ESB7130S	2 - 1.2 P 1 F CE	CE P EN166 F
ESB7138S	5 -2.5 P 1 F CE	CE P EN166 F
ESB7180S	5 -1.7 P 1 F CE	CE P EN166 F

Lens Marking Symbols

Code - field of use

2 or 3: UV filter
 5 or 6: Solar filter

Color perception

C: Unimpaired color perception

Protection class

1.2 - 6: Degree of visible light filtration

Optical class

1: High optical quality - no optical distortion

Mechanical Strength

F: Low energy impact, resists a 6 mm, .86 g at 45 m/s

Symbols

P: Manufacturer's mark
 N: Filter with anti-fog
 CE: Europe standard

Frame Marking Symbols

Symbols

CE: Europe standard
 P: Manufacturer's mark
 EN166: CE specification for protective eyewear

Mechanical Strength

F: Low energy impact



There's more to see at
PYRAMEXSAFETY.COM

(P) +44 (0) 1635 254220 | (E) info@pyramexeurope.com