



PYRAMEX
Perform At Your Peak™

Proximity® ANSI CE CSA



FOAM
PADDING



CO-INJECTED
TEMPLES

Flame resistant foam padding

Ultra lightweight spectacle – 26.3gm

Slim co-injected temples

| Part No. | Black Frame |
|---------------|---------------------------|
| SB9310ST ●●● | AF Clear H2X |
| SB9310STM ●●● | AF Clear H2MAX |
| SB9323ST ●●● | AF Dark Gray H2X |
| SB9323STM ●●● | AF Dark Gray H2MAX |
| SB9330ST ●●● | AF Amber H2X |
| SB9380ST ●●● | AF I/O Mirror |



vimeo.com/pyramex/h2max



There's more to see at
PYRAMEXSAFETY.COM

(P) 800.736.8673 | (F) 901.861.4967

All safety eyewear meets ANSI Z87.1+ standards (●) and provide 99% protection from harmful UV rays. All lenses are hard coated polycarbonate scratch-resistant unless otherwise noted. Some options meet European [EN166] (●) and Canadian [CSA Z94.3] (●) standards.

Proximity®

General Specifications

Weight: 26.3 gm
 PD: 64 mm
 Bridge: 16.5 mm
 Lens base: 9.5 curve
 Lens size diagonal: 75.8 mm
 Lens size vertical: 50.4 mm
 Lens thickness: 1.6 mm
 Overall length (lens - tip): 161 mm
 Overall width (hinge - hinge): 135 mm
 Closest point between temple tips: 77 mm
 Closest point between lens: 14.5 mm

Materials

Lens: polycarbonate
 Temples: polycarbonate & thermoplastic elastomers (TPE)
 Hinge: polycarbonate
 Screw: stainless steel
 Foam gasket: nylon & ethylene-vinyl acetate (EVA) foam

| Part No. | Lens Markings | Frame Markings |
|-----------|-----------------|------------------------------------|
| SB9310ST | P Z87 + U6 | P Z87 + / P c SEI CAN/CSA Z94.3-15 |
| SB9310STM | P Z87 + U6 | P Z87 + / P c SEI CAN/CSA Z94.3-15 |
| SB9323ST | P Z87 + S | P Z87 + / P c SEI CAN/CSA Z94.3-15 |
| SB9323STM | P Z87 + S | P Z87 + / P c SEI CAN/CSA Z94.3-15 |
| SB9330ST | P Z87 + U6 | P Z87 + / P c SEI CAN/CSA Z94.3-15 |
| SB9380ST | P Z87 + U6 L1.7 | P Z87 + / P c SEI CAN/CSA Z94.3-15 |

Lens Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact
 S: Special purpose
 UV Filter Transmittance
 U6: .01% max effective far UV • .1% max near UV
 Visible Light Filters
 L1.7: 55% max visible light

Frame Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact
 c SEI CAN/CSA Z94.3-15: CAN/CSA standard for eye and face protection devices



There's more to see at
PYRAMEXSAFETY.COM

(P) 800.736.8673 | (F) 901.861.4967