

TurboShearHD



Malco®

Work. Perform. Outlast.
Limited Lifetime Warranty



Long-lasting blades make fast, smooth trim cuts and tight circular or rectangular cuts in metal ductwork, metal roofing, and metal building panels. This well-tailored attachment quickly inserts into the chuck of a corded or cordless drill to make fast straight, curved, or square cuts in most common sheet metals. A sleek, lightweight aluminum cast shear head and molded drill clamp allow maximum portability and ease to go wherever the work is.



TSHD
Pat. No. 9,649,702

360° Rotating Head

The 360-degree rotating head allows users to position and lock the drill so it doesn't interfere with material for quick, hassle-free cuts every time!



Drill Requirements:
1/4 in. (6.35 mm) Chuck,
Min. 14.4V - DC, Max 7A-AC

Capacities: Spiral Duct 20 ga. 0.040 in. (1.02 mm) / Galvanized Steel - 18 ga. 0.052 in. (1.32 mm) / Mild Steel - 18 ga. 0.048 in. (1.22 mm)

Catalog Number	Description	Net Wt. oz. (g)	Net Wt. lbs. (kg)
TSHD	TurboShear Heavy-Duty	—	2.2 (1.00)
Replacement Parts			
TSDC	TurboShear Drill Clamp	8 (227)	—
TSCG	TurboShear Chuck Guard	.96 (27)	—
TSHDRB	TurboShear Heavy Duty Replacement Blades	7.04 (200)	—